

TRUE RMS MULTIMETER WITH USB INTERFACE

Just Added

TENMA®

Features:

Large 19,999 count backlit display with analog bargraph

- **True RMS Measurement**
- **Selectable auto/manual range**
- **Data logging and data recall**
- **Max/min mode**
- **Sleep mode**

Specifications: Range

DC voltage: 200mV, 2V, 20V, 200V, 1000V

- **AC Voltage: 2V, 20V, 200V, 1000V**
- **DC Current: 200uA, 2000uA, 20mA, 200mA, 10A**
- **AC Current: 200uA, 2000uA, 20mA, 200mA, 10A**
- **Resistance: 200Ω, 2KΩ, 20KΩ, 200KΩ, 2MΩ, 20MΩ**
- **Capacitance: 20nF, 200nF, 2uF, 20uF, 200uF, 2mF, 20mF**
- **Temperature: -40°F - 1832°F**
- **Frequency: 20Hz, 200Hz, 2KHz, 20KHz, 200KHz, 2MHz, 20MHz, 200MHz**
- **Duty Cycle: 10% - 90%**
- **Current Loop: 4 - 20mA displays 0 - 100%**
- **Input Impedance: 10MΩ**
- **Dimensions: 8" x 3 5/8" x 1 1/2" (H x W x D)**



Full function multimeter offers a variety of ranges for every service application and an optically isolated USB interface. Includes four foot opto-coupled USB cable, data logging software, standard test leads, short clip leads for accurate capacitance measurement, alligator clip adaptors, standard 9V battery, soft case and instruction manual.

Mfg. Part No.	Description
72-7730	True RMS Multimeter with USB Interface